

# **MASSIVE 240S - 50 HP**

#### PERFORMANCE

Maximum engine power at 2,250 rpm 50 hp\* Maximum torque at 1,400 rpm 172 Nm Maximum PTO power at rated 44 hp\*\* engine speed

- \* Certified to BU AU 141a: (1971)
- \* Manufacturer's estimate

ENGINE	
Туре	Diesel AD 3,1524
No. Of Cylinders	3
Injection	Direct
Bore	91.4mm
Stroke	127.0 mm
Capacity	2.5
Compression ratio	16.5 : 1
Aspiration	Natural
Starting Aid	Thermostat
Throttle control	Hand and foot
Cooling	Water
Air Cleaner Type	Oil bath
Air Pre-Cleaner	Over Bonnet, air swirl
Fuel filter	Dual, high capacity
Exhaust	Vertical

# **ELECTRICS**

Voltage	12 V, Negative Earth
Battery	110 Ah
Starter	2.2 kW
Alternator	32 Amp

#### CLUTCH

Reverse 1

Reverse 2

Type **Dual clutch** 305 x 254 mm Diameter

#### TRANSMISSION

Туре	Sliding Spur
Number of gears	& forward, 2 reverse
Road speed at 2,250 engine	rpm with
12.4 / 11 - 28 rear tyrea	

Gear		Speed (kph)
Forward 1	(first low)	2.7
Forward 2		3.9
Forward 3		5.3
Forward 4		7.2
Forward 5	(first high)	10.6
Forward 6		15.6
Forward 7		21.3
Forward 8		28.6

(low)

(high)

#### **POWER TAKE OFF**

Туре	Live
Engine speed at 240 PTO rpm	1,789 rpm
Shaft diameter	35 mm
no. Of splines	6

#### **HYDRAULICS**

Functions	Draft control,
	Position control,
	Response control,
	Constant pumping

Pump Type	Reciprocating
Maximum Oil Flow	Ferguson Pump 16:/mix
Maximum Pressure	19.2 Mpa

ower links horizontal	7 - 5	`
Lower Links	With cat. I	& 1

#### **FRONT AXLE**

Max. Lift capacity with

Box Section,	11 67	Туре
∆diustable		$\cap$ $\setminus$

### STEERING

Steering	Hydrostatic
----------	-------------

# **REAR AXLE AND BRAKES**

Brake Type	Out board drum brakes
Actuation	Mechanical,
	Independent or locked
	together
Parking Brake	Hand lever operated
Differential lock	Mechanical

## INSTRUMENTATION

Gauges	Technometer,
	Hourmeter, Feul level,
	Battery condition &
	Water temeprature

Warning lights	Direction indicators,
	Battery charge,
	Headlight main beam,
	Low engine oil
	pressure & Brake lights

# **TYRES**

3.6

14.5

Front	6.00 - 16 (6PR)
Rear	12.4 / 11 - 28 (6PR

#### TRACK ADJUSTMENT

FIOIIL	1,245 - 1,854 mm
Rear	1 321 - 1 930 mm

1,321 - 1,930 mm

#### **WEIGHTS AND DIMENSIONS**

## Weight

Gross Weight	1,690	kς
Gross Weight	1,690	k

#### **Dimensions**

Wheel base	1,892 mm
Overall Length	3,260 mm
Overall width (min)	1,651 mm

# Height

1,415 kg

interchangeable balls

Over exhaust	2,145 mm
Over steering wheel	1,410 mm

## **Turning Circle**

With brakes	5,560 mm
Without brakes	6,200 mm

#### **Ground Clearance**

Under	gear box	338 mm

## CAPACITIES

CALACITIES	
Fuel tank	47.5
Engine pump	6.8
Cooling system	10.2
Hydraulic system	33.0
Steering box	0.9
Oil bath air-cleaner	0.65

#### STANDARD EQUIPMENT

Weight frame without weights, standard tool box with set of tools, Top link, Top link end cat-i, Cat-I & II balls, Check chains, Spring operator's Manual

#### OPTIONAL EQUIPMENT

Front end weights, swinging drawber, sun Canopy.