

# **MASSIVE 345** - 50 HP

### PERFORMANCE

Maximum engine power at 2,250 rpm  $50 \text{ hp}^*$  Maximum torque at 1,400 rpm 172 Nm Maximum PTO power at rated  $44 \text{ hp}^{**}$  engine speed

- \* Certified to BU AU 141a: (1971)
- \* Manufacturer's estimate

ENGINE	
Туре	Diesel AD 3,1524
No. Of Cylinders	3
Injection	Direct
Bore	91.4mm
Stroke	127.0 mm
Capacity	2.5
Compression ratio	16.5 : 1
Aspiration	Natural
Starting Aid	Thermostat
Throttle control	Hand and foot
Cooling	Water
Air Cleaner Type	Oil bath
Air Pre-Cleaner	Over Bonnet, air swirl
Fuel filter	Dual, high capacity
Exhaust	Vertical

### **ELECTRICS**

Voltage	12 V, Negative Earth
Battery	110 Ah
Starter	2.2 kW
Alternator	32 Amp

## CLUTCH

 Type
 Dual clutch

 Diameter
 305 x 254 mm

### **TRANSMISSION**

Type	Sliding Spur
Number of gears	& forward, 2 reverse
Road speed at 2,250 engine rpn	n with

12 4 / 11 - 28 rear tyrea

12.4 / 11 - 20	rear tyrea	
Gear		Speed (kph)
Forward 1	(first low)	2.7
Forward 2		3.9
Forward 3		5.3
Forward 4		7.2
Forward 5	(first high)	10.6
Forward 6		15.6
Forward 7		21.3
Forward 8		28.6
Reverse 1	(low)	3.6
Reverse 2	(high)	14.5

### POWER TAKE OFF

Туре	Live
Engine speed at 240 PTO rpm	1,789 rpm
Shaft diameter	35 mm
no. Of splines	6

### **HYDRAULICS**

Draft control,
sition control,
onse control,
stant pumping

Pump Type	Reciprocating
Maximum Oil Flow	Ferguson Pump 16:/mix
Maximum Pressure	19.2 Mpa
Max. Lift capacity with	1,415 kg

lower links horizontal	1				
Lower Links	Wi	th cat.	I	&	Ш

interchangeable balls

### FRONT AXLE

Box Section,	(5)	Туре
Adjustable		$\cup$ $\cap$

### STEERING

lydrostatic
ł

# REAR AXLE AND BRAKES

Brake Type	Out board drum brakes
Actuation	Mechanical,
	Independent or locked
	together
Parking Brake	Hand lever operated
Differential lock	Mechanical

### INSTRUMENTATION

Gauges	Technometer,
	Hourmeter, Feul level,
	Battery condition &
	Water temeprature

Warning lights	Direction indicators,
	Battery charge,
	Headlight main beam,
	Low engine oil
	pressure & Brake lights

TIKES	
ront	6.00 - 16 (6PR)
Rear	12.4 / 11 - 28 (6PR)

### TRACK ADJUSTMENT

1.245 - 1.854 mm

# Rear 1,321 - 1,930 mm

## WEIGHTS AND DIMENSIONS

## Weight

Front

Gross Weight	1,690 kg
--------------	----------

### **Dimensions**

Wheel base	1,892 mm
Overall Length	3,260 mm
Overall width (min)	1,651 mm

### Height

Over exhaust	2,145 mm
Over steering wheel	1,410 mm

# **Turning Circle**

With brakes	5,560 mm
Without brakes	6,200 mm

### **Ground Clearance**

Under gear	box	338 mm
------------	-----	--------

### CAPACITIES

Fuel tank	47.5 I
Engine pump	6.8 I
Cooling system	10.2 I
Hydraulic system	33.0 I
Steering box	0.9 I
Oil bath air-cleaner	0.65 I

### STANDARD EQUIPMENT

Weight frame without weights, standard tool box with set of tools, Top link, Top link end cat-i, Cat-I & II balls, Check chains, Spring operator's Manual

### OPTIONAL EQUIPMENT

Front end weights, swinging drawber, sun Canopy.